

Fast.

blink

MODE 3 2x22kW

AC Fast Charger

The fastest charging station and innovative income-producing product that appeals to your customers with maximum flexibility and control for you.

DOUBLE SOCKET • VARIABLE CHARGING CURRENTS MULTIPLE UNIT NETWORK

AC MODE 3 Benefits

- Double socket
- Controllable output power
- Future-proof, stylish and compact design
- Low installation and maintenance cost
- Increased reliability
- Blink Network and OCCP integration

Product Details

Output Sockets	2
Connectors	Type 2
Output Power	44 kW (2 x 22 kW)
Input Voltage	230 V AC single phase, 400 V AC 3phase
Maximum Input Current	64 A (32 A + 32 A)
Frequency	50 Hz
Display	4.3" TFT color screen
Energy Measurement	2 x MID meters
IP/IK Protection	IP54/IK10 (display IK08)
Operating Temperature	-25°C to 50°C
Network Connections	3G, WiFi, Ethernet
RFID	Mifare Classic, Mifare DESfire
Communication Protocols	OCCP 1.6J
Electrical Protection	Short circuit, Over voltage, RCD
Weight	33 kg
Dimensions	1400 (h) x 320 (w) x 215 (d) mm
Standards	IEC-61851-1, IEC-61851-21-2, IEC-61000
European Directives	Low Voltage Directive: 2014/35/EU EMC Directive: 2014/30/EU
Certification	CE



blink

BlinkCharging.gr
+30 210 7232862